



Although Re~mov contains only 1% HAPs it is considered flammable. Always use in well ventilated areas away from possible sparks & open flame. For more information please consult the MSDS on our [website](http://www.silicone-remover.com).

Directions For Use:

As a rule of thumb, products that do not harden, i.e., most caulks, contact adhesives, labels, decals, tape residue, gum, sap, tar, wax can be removed with **Re~mov™**. Hardened products such as Super Glue, two part epoxies, urethane floor coatings and varnishes cannot be removed with **Re~mov™**

Caulking

For silicone, polyurethane, and polysulfide caulks, first cut away any loose caulking then work **Re~mov™** from the edge(s) of the bond with a putty knife or scraper. **Re~mov™** will work its way under the caulk and release the bond. If residue remains, simply re-apply to the area and wipe it clean with a terry type cloth. If you apply **Re~mov™** to an area by mistake, either wipe dry or let the **Re~mov™** evaporate, the caulking will not be affected.

Contact Cement/Glue/Liquid Nails™

Coat the area with **Re~mov™** and let it sit. The longer it remains on the adhesive the easier your job becomes. Then wipe the area with a clean cloth. If any residue remains, repeat the first step. When using **Re~mov™** to remove carpet or headliners, apply the surface heavily, wait at least 15 minutes and test a portion of the item to be removed. If the item remains secure, re-apply **Re~mov™** and wait an additional 15 minutes before removing the item. With Liquid Nails™ if wet: just apply and wipe, if dry: apply and let stand for 30 minutes minimum then pick up and dispose of Liquid Nails™ residue.

Polyurethane Expanding Foams

Apply **Re~mov™** to the contaminated area with and wipe with a clean cloth, note once the foam has cured [6 hrs plus] the **Re~mov™** will **not** remove the residue.

Tape/Labels/Stickers/Decals/Pin Stripping/Protective Film

First, apply **Re~mov™** to the edges of the item to be removed and let sit for a minute. **Re~mov™** penetrates from the edges inward. Use a sharp object to work the edges and re-apply **Re~mov™** as needed. Once there is enough material to grab, slowly begin pulling the item away from the adhesive while adding **Re~mov™**. It should pull away with ease.

Gum

To remove gum from carpets, clothing or fabric, just apply **Re~mov™**, wait a minute, and rub the area with your fingers or a stiff nylon brush, gum will ball up, then remove with a clean dry cloth.

Sap/Tar/Grease/Oil

Sap, Tar, Grease and Oil will readily dissolve in **Re~mov™**, just apply, wait, and wipe.



Access these directions on your smart phone.

In case of emergency call:

ChemTel Inc. 1 (800) 255-3924
(Canada & USA).
International. + 01 (813) 248-0585